



CORTEC
CORPORATION

Environmentally Safe VpCI®/MCI® Technologies

ElectriCorr® VpCI®-239 Multi-Metal Cleaner/Protector

■ 제품 설명

ElectriCorr VpCI-239는 옥외 환경에서 사용할 수 있는 다기능 세정 및 부식 방지제입니다. 금속 표면의 오일, 먼지 및 찌든 때, 왁스와 기타 오염물질을 손쉽게 제거하는 동시에 처리된 표면에 부식 방지 성능을 제공합니다.

ElectriCorr VpCI-239는 산업 지역, 해양 환경 및 열대 지역과 같은 가혹한 환경 조건으로부터 금속을 보호할 수 있도록 매우 얇은 보호 피막을 형성합니다.

제품에 포함된 기화성 부식 방지 성분은 지속적으로 기화하여 일반적인 도포 방식으로는 접근하기 어려운 부위까지 보호합니다.

ElectriCorr VpCI-239는 대부분의 플라스틱, 탄성중합체 및 기타 비금속 소재와 안전하게 사용할 수 있습니다.

ElectriCorr VpCI-239로 처리한 부품과 장비를 적절하게 포장하면, 필요할 때 즉시 사용할 수 있는 상태로 보관할 수 있습니다.

ElectriCorr VpCI-239는 CFC 및 1,1,1-트리클로로에탄을 함유하지 않으며, 제품 적용 즉시 부식 방지 효과를 제공합니다.

UFI: 3A20-H08X-K003-H2KY

■ 포장 및 보관

ElectriCorr VpCI -239는 267g 에어로졸 스프레이(박스당 6캔, 19리터 플라스틱 통, 드럼으로 제공됩니다).

제품의 최적 성능을 유지하기 위해 직사광선을 피해 4-38 °C의 실내에서 보관하십시오.

보관 기한: 3년

VpCI® EMITTING SYSTEMS & ELECTRONIC PRODUCTS



■ 제품 특징

- 우수한 옥외 부식 방지 성능
- 실내 적용 가능
- 빠르게 건조되는 비접촉성 부식 방지 피막 형성
- 먼지 및 찌든 때, 오일, 왁스와 기타 오염물질을 효과적으로 제거
- 철금속 및 비철금속에 즉각적인 부식 방지 효과 제공
- 현장 유지보수 작업 최소화
- 기존 방청제보다 경제적인 비용으로 향상된 부식 방지 성능 제공
- CFC 및 1,1,1-트리클로로에탄 무함유
- 접근하기 어려운 부위에 기화성 부식 방지 효과 제공
- 수치화선과 침투성을 갖춘 보호 피막 형성

■ 주요 적용 분야

- 세정된 금속 표면, 부품 및 장비의 보존
- 수계 세정 후 탈수 및 수분 제거
- 공정 단계 사이의 임시 부식 방지
- 펌프 보존
- 전기 모터 보존
- 엔지니어링 플라스틱, 탄성중합체 및 기타 비금속 소재와 접촉하는 부위
- 옥외 발전기 및 정전박스
- 실내 · 외 전기 콘센트 및 전기 접속부

■ 적용 방법

보호가 필요한 부위 전체에 제품이 묻도록 매우 가볍고 얇게 분무합니다.

건조 시간은 약 21 °C의 온도, 상대습도 50% 조건에서 약 1~2시간입니다.

주의사항: 제품을 과도하게 분사하면 두꺼운 피막이 형성되어 흘러내릴 수 있으며, 표면이 완전히 건조되지 않고 젖은 상태로 남을 수 있습니다.

ElectriCorr® VpCI®-239 Multi-Metal Cleaner/Protector

■ 표준 시험 방법

ASTM D-1748	Humidity Cabinet	300+ 시간
-------------	------------------	---------

4119 White Bear Parkway, St. Paul, MN 55110 USA
Phone (651) 429-1100, Fax (651) 429-1122
Toll Free (800) 4-CORTEC
info@cortecvci.com
http://www.cortecvci.com



LIMITED WARRANTY

All statements, technical information and recommendations contained herein are based on tests Cortec® Corporation believes to be reliable, but the accuracy or completeness thereof is not guaranteed.

Cortec® Corporation warrants Cortec® products will be free from defects when shipped to customer. Cortec® Corporation's obligation under this warranty shall be limited to replacement of product that proves to be defective. To obtain replacement product under this warranty, the customer must notify Cortec® Corporation of the claimed defect within six months after shipment of product to customer. All freight charges for replacement products shall be paid by customer.

Cortec® Corporation shall have no liability for any injury, loss or damage arising out of the use of or the inability to use the products.

BEFORE USING, USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR ITS INTENDED USE, AND USER ASSUMES ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH. No representation or recommendation not contained herein shall have any force or effect unless in a written document signed by an officer of Cortec® Corporation.

THE FOREGOING WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES, EXPRESS, IMPLIED OR STATUTORY, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE. IN NO CASE SHALL CORTEC® CORPORATION BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.